



**Product #:** 7032760

**Order Symbol:** UL PC 122008

**Description:** Enclosure, PC

**Remarks:** Grey cover

| Dimensions | Height | Width | Depth |
|------------|--------|-------|-------|
| Inch       | 7.9    | 4.7   | 3     |
| mm         | 200    | 120   | 75    |

### Materials

|                  |                      |
|------------------|----------------------|
| Material:        | Polycarbonate        |
| Base color:      | RAL 7035 -light grey |
| Cover color:     | RAL 7035 -light grey |
| Gasket material: | Polyurethane         |

### Temperatures

|                              |             |
|------------------------------|-------------|
| Temperature °F (short term): | -40 ... 250 |
| Temperature °F (continuous): | -40 ... 175 |
| Temperature °C (short term): | -40 ... 120 |
| Temperature °C (continuous): | -40 ... 80  |

### Ratings

|  |                               |
|--|-------------------------------|
| Ingress Protection (EN 60529):         | IP66IP67                      |
| Impact Resistance (EN 62262):          | IK07IK08                      |
| Electrical insulation:                 | Totally insulated             |
| Halogen free (DIN/VDE 0472, Part 815): | No                            |
| UV resistance:                         | UL 508                        |
| Flammability Rating:                   | UL 746C 5"                    |
| Glow Wire Test (IEC 60695):            | 960 °C                        |
| UL/cUL Type:                           | NEMA Type 1, 4, 4X, 12 and 13 |