


HEAD TO HEAD Enclosures

System Integration

1
Fibox Enclosures



2
Hoffman,
A Pentair Co.



3
Rittal Corp.



4
Vynckier Enclosures



	<p>MXN enclosures provide protection for electronics operating in hostile environments. 240 standard size variations plus custom molds for high volume applications are offered. www.fiboxusa.com 888-342-6987</p>	<p>QLINE Type 4X enclosures house sensitive components in wet, dusty and/or corrosive environments where electromagnetic compatibility and/or system security is required. www.hoffmanonline.com 763-422-2211</p>	<p>PK Series of polycarbonate enclosures provide corrosion-proof packaging for any application where components require protection against dust and liquids. They can also be used in harsh industrial environments and for controls or electronic equipment. www.rittal-corp.com 800-477-4000</p>	<p>VM Series enclosures, with opaque cover and knockouts are made of corrosion resistant Valox, RAL 7035 color. There are molded internal bosses for back panel, mounting of components or DIN rail. www.enclosuresonline.com 713-374-7850</p>
Size Range	240 standard, screw cover H x W-4" x 4" to 10" x 7". Depths range from 1.4" to 7"	78 standard, screw cover H x W-3" x 5" to 10" x 7" Depth range from 2.6" to 5.6"	47 standard, screw cover H x W-2" x 2" to 14" x 10" Depth range from 1.4" to 6.5"	40 standard, screw cover H x W-3" x 5" to 7" x 7" Depth range from 3.0" to 6.0"
Ingress Rating	Type 1, 4, 4X, 6, 12 and 13 IP66/67	Type 4, 4X, 6, 12 and 13 IP67	Type 4X IP66	Type 3, 3R, 4, 4X, 12 and 13 IP66
Temperature Range (Continuous Operation)	-40 to 175 °F (Polycarbonate) -40 to 140 °F (ABS)	-31 to 180 °F (Polycarbonate) -4 to 125 °F (ABS)	-39 to 175 °F (Polycarbonate)	Up to 280 °F (Valox base/cover) -40 to 248 °F (Polycarbonate cover)
Transparent Covers	Yes. All sizes available with opaque or transparent covers.	Yes. All sizes available with opaque or transparent covers.	Yes. Most sizes available with opaque or transparent covers.	Yes. All sizes available with opaque or transparent covers.
Material Options	Polycarbonate or ABS Gasket-PUR, TPE and silicone	Polycarbonate or ABS Gasket-PUR	Polycarbonate Gasket-PUR	Valox or Polycarbonate Gasket-PUR
Knockouts	Yes. Standard Metric KO's available.	No	No	Yes. Standard 3/8" and 1" KO's available.
Accessories	Mounting panels, DIN rails, hinged inner panels, vents, hinges, mounting feet, glands, window kits and membrane keypad covers.	Mounting panels, DIN rails, hinges, mounting feet and brass inserts	Mounting panels, DIN rails, hinges, mounting brackets and twist lock fasteners.	Mounting panels, mounting feet, vents and window kits.
RoHS Compliant	Yes	By July 2006	Yes	Not specified
Certifications	UL, cUL, FIMCO, DNV, Gost R	UL, cUL, CSA	Bureau Veritas	UL, CSA
Customization	Yes. Factory modifications by CNC or custom mold inserts.	Yes. Factory modification by CNC.	Yes. Factory modification by CNC.	Yes. Factory modification by CNC.
Custom Molding	Yes. Custom covers mated to standard MXN bases. Color and material options.	No custom molds. Yes custom colors	Not specified.	Yes custom logos. Yes custom colors.

Posted from IAN Inside Products, April/May 2006. Copyright © Reed Business Information, a division of Reed Elsevier, Inc. All rights reserved.
Page layout as originally published in IAN Inside Products has been modified.



Fibox Enclosures
Glen Burnie, MD

Tel: (888) 342-6987 • Fax: (410) 760-8686
sales@fiboxusa.com • www.fiboxusa.com