



Product #: 7022741

Order Symbol: UL PCT 162515

Description: Enclosure, PC

Remarks: Clear Cover

| Dimensions | Height | Width | Depth |
|------------|--------|-------|-------|
| Inch | 9.8 | 6.3 | 5.9 |
| mm | 250 | 160 | 150 |

Materials

| | |
|------------------|----------------------|
| Material: | Polycarbonate |
| Base color: | RAL 7035 -light grey |
| Cover color: | Clear |
| Gasket material: | Polyurethane |

Temperatures

| | |
|------------------------------|-------------|
| Temperature °F (short term): | -40 ... 250 |
| Temperature °F (continuous): | -40 ... 175 |
| Temperature °C (short term): | -40 ... 120 |
| Temperature °C (continuous): | -40 ... 80 |

Ratings

| | |
|--|-------------------------------|
| Ingress Protection (EN 60529): | IP66IP67 |
| Impact Resistance (EN 62262): | IK07IK08 |
| Electrical insulation: | Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815): | No |
| UV resistance: | UL 508 |
| Flammability Rating: | UL 746C 5" |
| Glow Wire Test (IEC 60695): | 960 °C |
| UL/cUL Type: | NEMA Type 1, 4, 4X, 12 and 13 |