



# ARCA JIC

Order Symbol: AR24208CHSSLY

Description: Yellow PC Enclosure (painted on outside)

Remarks : Hinged Opaque Cover w/S.S. Lockable Latch

Hinged cover base with 10-32 brass inserts, latched cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.) Metal mounting foot kit. Accessory 10-32 screws for panel mounting.



**SAMPLE IMAGE**

Support items:

[Dimensional drawing \(mm\)](#)

[Cad-files \(registration needed\)](#)

[Sales@fiboxusa.com](mailto:Sales@fiboxusa.com)

| Dimensions | Length | Width | Height |
|------------|--------|-------|--------|
| Inch       | 24.1   | 20.1  | 8.1    |
| mm         | 611.0  | 510.0 | 205.0  |

| Materials        |                            |
|------------------|----------------------------|
| Material:        | Polycarbonate              |
| Base Color:      | RAL 1026 - LUMINOUS YELLOW |
| Cover Color:     | RAL 1026 - LUMINOUS YELLOW |
| Gasket material: | Polyurethane               |

| Temperature                  |                |
|------------------------------|----------------|
| Temperature C° (short term): | -40° - 120° C" |
| Temperature C° (continuous): | -40° - 80° C"  |
| Temperature F° (short term): | -40° - 250° F  |
| Temperature F° (continuous): | -40° - 175° F  |

| Ratings                                |                  |
|--|------------------|
| NEMA Class                             | NEMA 4, 4X, & 12 |
| Ingress Protection (EN 60529):         | IP66/IP67        |
| Impact Resistance (EN 62262):          | IK 09            |
| Electrical insulation:                 | Fully Insulated  |
| Halogen free (DIN/VDE 0472, Part 815): | 1                |
| UV Resistance:                         | UL 508           |
| Flammability Rating:                   | UL 508           |
| Glow Wire Test (IEC 695-2-1) °C:       | 960              |

Product is connected to following catalogs:  
Fibox Enclosures : ARCA : AR 24208